

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. This Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY Mesquite Man's Cactus Juice Stabilizing Resin	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

Section I

Supplier's Name TurnTex Woodworks	Emergency Telephone Number 1-800-222-1222
Address (Number, Street, City, State, and ZIP Code) 531 Hunter Ridge San Marcos, TX 78666	Telephone Number for Information 512-738-0775
	Date Prepared 2/03/11
	Signature of Preparer (optional)

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	%(optional)
Mixed Methacrylate Esters Proprietary Mixture	90-95
Surfactant Proprietary Mixture	5-10
All components listed in TSCA inventory	

Section III - Physical/Chemical Characteristics

Boiling Point	>300°F	Specific Gravity (H ₂ O = 1)	1.0
Vapor Pressure (mm Hg.)	Less than 5 at 72°F	Melting Point	N/A
Vapor Density (AIR = 1)	N/DA	Evaporation Rate (Butyl Acetate = 1)	N/DA
Solubility in Water Slight			
Appearance and Odor Clear, colorless with a mild odor			

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) >200°F	Flammable Limits	LEL N/DA	UEL N/DA
Extinguishing Media: Foam, CO ₂ , or dry powders.			
Special Fire Fighting Procedures Wear suitable protective equipment. Use water spray/fog for cooling			
Unusual Fire and Explosion Hazards N/A			

Section V - Reactivity Data

Stability	Unstable	Conditions to Avoid High temperatures, direct sunlight and UV radiation
	Stable X	(Under normal conditions)
Incompatibility (Materials to Avoid) Reducing agents.		
Hazardous Decomposition or Byproducts (non thermal) zone		
Hazardous Polymerization	May Occur X	Conditions to Avoid: If over-catalyzed or insufficiently aerated after catalyzing This polymerization is exothermic
	Will Not Occur	

Section VI - Health Hazard Data

Threshold Limit Value: ACGIH & OSHA: Carcinogens (NTP, IARC, OSHA): None
Effects of overexposure: May cause irritation to eyes, respiratory system and skin. May cause sensitization by skin contact. Prolonged/repeated exposure may cause severe dermatitis on prolonged contact in sensitive individuals.
Emergency and First Aid Procedures: Rinse eye immediately with plenty of water for 15 – 20 min. Obtain medical attention. Wash skin with plenty of soap and water for 15 minutes. If sticky, use a waterless cleaner first. Seek medical attention if irritation develops. After inhalation, remove to fresh air and give O ₂ /artificial respiration as necessary. After ingestion, do not induce vomiting, give water to drink. See medical attention.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled: Soak up with an inert absorbent. Store in a partly filled, closed container until disposed.
Waste Disposal Method: Contaminated product/soil/water may be hazardous waste due to the potential for internal heat generation. Landfill at permitted sites. Use registered transporters. Burn concentrated liquids in systems that use compatible fuel. Ensure emissions comply with regulations. Dilute aqueous waste may be biodegradable. Ensure effluent complies with applicable regulations.

Section VIII - Control Measures

Respiratory Protection (Specify Type): For high concentrations: Approved air purifying or supplied air respirator in positive mode.		
Ventilation	Local Exhaust Recommended	Special: Suction exhaust of vapors is recommended if large quantities are involved
	Mechanical (General) N/A	Other: None
Protective Gloves: Chemical resistant gloves.		Eye Protection: Splash goggles or Safety Glasses.
Other Protective Clothing or Equipment: Safety shower and eye wash should be in work area.		

Section IX - Special Precautions

Precautions to be taken in Handling and Storing: Store sheltered from light at temperatures below 100°F in original container.
Other Precautions: Keep away from strong oxidizers, radiation, and other initiators. Prevent long storage times.

Section X – Regulator Information

All ingredients are listed or exempt from listing on TSCA Inventory.
Estimated HMIS Code: Health Hazard (2) Fire Hazard (1) Reactivity (2)

Section XI – Transportation

DOT (49 CFR 172) Domestic Ground Transportation: Proper Shipping Name: Unrestricted Hazard Class or Division: Unrestricted Identification Number: None Marine Pollutant: None IATA: Proper Shipping Name: Unrestricted Class or Division: Unrestricted UN of ID Number: None

Information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. Nothing herein shall be considered as recommending practices or products in violation of any patent, law or regulation. It is the user's responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. WE MAKE NO WARRANTIES REGARDING THE PRODUCTS AND DISCLAIM ALL EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.
